



## Material Safety Data Sheet

Product Name/Code SAMAN ALKYD STAINS / SAM-301 TO SAM-318	HMIS CODES health 1 flammability 0 reactivity 0
--	--

Section 1 Product and Company Identification	
Manufacturer's name Saman 3777472 Canada inc.	Emergency Telephone Number 819-751-2350
Address (Number, Street, City, State and ZIP Code) 1235, rue de L'Acadie Victoriaville (Québec) Canada G6T 1W4	Telephone Number for Information 819-751-2350
Date December 2007	Prepared by Yvan Désilets

Section 2 Hazardous Ingredients/Identity Information					
HAZARDOUS COMPONENTS NAME / CAS NO.	WT %	OSHA PEL	ACGIH TLV	ORAL LD50 (RAT)	DERMAL LD50 (RABBIT)
n-propoxy propanol (PP) / 1569-01-3	0.5-1.5	n/a	n/a	2000-4350 mg/kg	
dibasic esters (DBE) / mixture 1119-40-0, 627-93-0, 106-65-0	1-5	n/a	n/a	8191 mg/kg	>2250 mg/kg
1,2-propanediol / 57-55-6	1-5	n/a	5 mg/m <sup>3</sup>	20 mg/kg	20.8g/kg
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (TMB) / 25265-77-4	0.5 -1.5	n/a	n/a	6517 mg/kg	>15200 mg/kg
carbon black / 1333-86-4	0-0.5	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>	>8000 mg/kg	n/a

Section 3 Physical/Chemical Characteristics			
Appearance and Odor	coloured liquid, mild odor		
Specific Gravity (H <sub>2</sub> O = 1)	1.02-1.05	Viscosity Ford cup #4 (seconds)	30-35
pH	7.7-8.1	% Volatile by Weight	74 ± 2
Boiling Point (°F)	212-500	Melting Point (°F)	n/a
Vapor Pressure (mm Hg)	17.54 (H <sub>2</sub> O)	Vapor Density (AIR = 1)	7.5 (TMB)
Evaporation Rate (Butyl Acetate = 1)	0.21 (PP)	VOC (g/l)	250
Solubility in Water	miscible		

Section 4 Fire and Explosion Hazard Data			
Flash Point (Method Used) n/a	Flammable Limits	LEL n/a	UEL n/a
Extinguishing Media	foam, carbon dioxide, water spray, dry powder Use water spray to cool containers in fire area.		
Special Fire Fighting Procedures	Use self-contained breathing apparatus and full protective clothing.		
Unusual Fire and Explosion Hazards	none		

**Section 5 Reactivity Data**

Stability	stable under normal storage and use	Conditions to Avoid	none known
Incompatibility (Materials to Avoid)	oxidizing agents, strongly alkaline and strongly acid materials		
Hazardous Decomposition or Byproducts	Thermal decomposition will produce carbon dioxide and may yield carbon monoxide, oxides of nitrogen, etc.		
Hazardous Polymerization	will not occur	Conditions to Avoid	n/a

**Section 6 Health Hazard Data**

Route(s) of Entry	eye and skin contact, inhalation, ingestion
Health Hazards	This product may be an eye irritant. Prolonged or repeated contact may cause skin irritation. Prolonged exposure in poorly ventilated area may cause headache, dizziness and respiratory tract irritation. Ingestion may cause gastrointestinal irritation, nausea and diarrhea.
Carcinogenicity	no
Medical Conditions	none generally recognized
Emergency and First Aid Procedures	<p>Eye: Check for and remove any contact lenses. Immediately flush with plenty of water. Get medical aid.</p> <p>Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water.</p> <p>Inhalation: Remove to fresh air. Administer artificial respiration if necessary. Get medical aid.</p> <p>Ingestion: Do not induce vomiting. Give 1-2 glasses of water to dilute stomach contents. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Never give anything by mouth to an unconscious person.</p>

**Section 7 Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material Is Released or Spilled	Stop leak if without risk. Prevent entry into drains or watercourses. Absorb with an inert material and put in an appropriate waste disposal.
Waste Disposal Method	Dispose of in accordance with local, state and federal environmental control regulations.
Precautions to Be Taken in Handling and Storing	Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Store in a cool well-ventilated area. Keep from freezing. Keep out of reach of children.

**Section 8 Exposure Controls and Personal Protection**

Engineering controls	Provide adequate ventilation. Local exhaust in addition to general room ventilation may be required to meet exposure limit(s).
Personal Protection	<p>Respiratory: none required with normal use in well-ventilated area NIOSH approved respirator is advised for poorly ventilated areas.</p> <p>Eye/Face: Safety glasses, splash goggles.</p> <p>Skin: Wear chemical resistant gloves. Wear long legged, long sleeve work clothes. Launder contaminated clothing before reuse.</p>
Work/Hygienic Practices	Do not store, use, and/or consume foods, beverages, tobacco products or cosmetics next to material. Wash hands and face carefully after work.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.