

# MSDS Sheet # 4A - AC-516 & MM-516C Sprays

## SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Prepared: January 10, 2007  
Supersedes: All previous  
Manufacturer: Mayco Colors  
Division of Coloramics, LLC  
4077 Weaver Court South  
Hilliard, Ohio 43026  
United States of America

### Distributor Contacts:

USA \_\_\_\_\_ Local Phone \_\_\_\_\_  
EC \_\_\_\_\_ Local Phone \_\_\_\_\_  
Australia \_\_\_\_\_ Local Phone \_\_\_\_\_

IN CASE OF EMERGENCY PLEASE CONTACT YOUR LOCAL POISON CONTROL CENTER

Prepared by: MSDS department  
Information Telephone Number: 614-876-1171

Coloramics N-F Spray Sealers AC-516  
Magic Metallics MM-516C

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

### 1 N-BUTANE

CAS# 106-97-8

#### N-BUTANE

PCT BY WT: 7.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

#### EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 800 ppm  
COMPANY N.E.  
LD50(ORAL) N.A.  
LD50(DERMAL) N.A.  
LC50 658000 mg/m<sup>3</sup> (rat)

---

### 2 PROPANE

CAS# 74-98-6

#### PROPANE

PCT BY WT: 19.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

#### EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm  
ACGIH TLV-STEL NO INFORMATION  
LD50(ORAL) NOT APPLICABLE  
LD50(DERMAL) NOT APPLICABLE  
LC50 NO INFORMATION

---

3 AMORPHOUS PRECIPITATED SILICA

CAS# 112926-00-8

AMORPHOUS PRECIPITATED SILICA

PCT BY WT: 1.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA 10 mg/m3
ACGIH TLV-STEL NO INFO
LD50(ORAL) > 10000 mg/kg (rat)
LD50(DERMAL) NO INFORMATION
LC50 > 139 mg/m3 (rat)

4 ACETONE

CAS# 67-64-1

ACETONE

PCT BY WT: 34.0000 VAPOR PRESSURE: 231.000 MMHG @ 68F LEL 2.60

EXPOSURE LIMIT:

ACGIH TLV-TWA 750 ppm
ACGIH TLV-STEL 1000 ppm
OSHA PEL-TWA 750 ppm
OSHA PEL-STEL 1000 ppm
COMPANY N.E.
LD50(ORAL) 5340 mg/kg (rabbit)
LD50(DERMAL) 20000 mg/kg (rabbit)
LC50 70852 mg/m3 (rat)

5 GLYCOL ETHER PM ACETATE

CAS# 108-65-6

PROPYLENE GLYCOL METHYL ETHER ACETATE

PCT BY WT: 7.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA NOT ESTABLISHED
ACGIH TLV-STEL NOT ESTABLISHED
LD50(ORAL) 8500 mg/kg (rat)
LD50(DERMAL) 5000 mg/kg (rat)
LC50 5321 mg/m3 (rat)

6 TOLUENE

CAS# 108-88-3

TOLUENE

PCT BY WT: 24.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40

EXPOSURE LIMIT:

ACGIH TLV-TWA 50 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 50 ppm
COMPANY N.E.
LD50(ORAL) 636 mg/kg (rat)
LD50(DERMAL) 14124 mg/kg (rabbit)
LC50 7523 mg/m3 (mouse)

OTHER LIMITS:

Prop 65-Developmental-01/01/91

\*\*\*\*\*

This substance is classified as a hazardous air pollutant.

\*\*\*\*\*

This product contains no reported carcinogens or suspected carcinogens.

\*\*\*\*\*

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

May be fatal if swallowed.  
Harmful if inhaled.  
Harmful if absorbed through skin.  
Causes eye irritation.  
Causes skin irritation.  
Vapors irritating to eyes and respiratory tract.  
Extremely flammable liquid and vapor.  
Vapors may cause flash fire or explosion.  
Extremely flammable aerosol.  
Contents under pressure.

#### EYE:

May cause severe eye irritation.

#### SKIN:

May cause skin irritation.  
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).  
May be absorbed through the skin.

#### INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.  
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.  
Excessive inhalation of vapors can cause nasal and respiratory irritation.  
Breathing high concentrations of vapors may cause anesthetic effects.  
Liquid or vapor may be irritating to skin, eyes, throat or lungs.  
Prolonged inhalation of dusts containing free silica may result in the development of a disabling pulmonary fibrosis(lung disease) known as silicosis.  
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

#### INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.  
Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

#### CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Lung damage
- Liver damage
- Spleen damage
- Anemia
- Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Liver damage
- Cardiac abnormalities
- Liver abnormalities
- Kidney damage
- Blood damage

Reports have associated repeated and prolonged overexposure to solvents

with permanent brain and nervous system damage.  
Product contains toluene which may be harmful to the fetus based on animal studies.  
Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

#### SECTION 4: FIRST AID MEASURES

##### EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

##### SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

##### INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

##### INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

#### SECTION 5: FIRE FIGHTING MEASURES

##### FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint . . . . . : Less Than -25 øF

Explosion Level . . . . . : Low (LEL) - 1.3  
High (UEL)- 13.1

##### EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

##### FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat.

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst.

Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

##### CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

## SECTION 7: HANDLING AND STORAGE

### HANDLING:

Wash hands thoroughly after handling.

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

### STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

### RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

### SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

### EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

### OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

### HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

|                                      |                               |
|--------------------------------------|-------------------------------|
| Vapor Pressure . . . . .             | : 5585.20 mm Hg @ 20 C        |
| Vapor Density . . . . .              | : -N/A                        |
| Boiling Range . . . . .              | : Lower - 1.0 øF              |
|                                      | Higher - 999.0 øF             |
| Specific Gravity . . . . .           | : .745                        |
| Formula Weight per Volume . . . . .  | : 6.2004 LB/GL                |
| VOC (Calculated, LB/GAL) . . . . .   | : 4.973                       |
| VOC (Calculated, GM/L). . . . .      | : 595.91                      |
| Percent Volatile by Weight. . . . .  | : 90.1457                     |
| Percent Volatile by Volume . . . . . | : 93.9098                     |
| Evaporation Rate . . . . .           | : 7.700 (n-Butyl Acetate = 1) |
| Viscosity . . . . .                  | : -N/A                        |

## SECTION 10: STABILITY AND REACTIVITY DATA

**CONDITIONS TO AVOID:**

Avoid contact with heat, sparks, and open flame.

Product may explode if heated. Keep cool, avoid exposure to heat.

**INCOMPATIBILITIES:**

Strong oxidizing agents.

**DECOMPOSITION:**

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

**POLYMERIZATION:**

No hazardous polymerization will occur under normal conditions.

**STABILITY:**

The product is stable under normal storage conditions.

**SECTION 11: TOXICOLOGY INFORMATION**

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

**SECTION 12: ECOLOGICAL INFORMATION**

No specific ecological information is available for this product.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:**

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

**SECTION 14: TRANSPORTATION INFORMATION**

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

**SECTION 15: REGULATORY INFORMATION**

**SARA 313 INFORMATION:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOLUENE

CAS# 108-88-3 PCT BY WT: 23.5440

---

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:  
Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

----- CHEMICAL NAME ----- CAS NUMBER

---

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

----- CHEMICAL NAME ----- CAS NUMBER

---

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16: ADDITIONAL INFORMATION

This information is furnished with out warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained from sources believed to be accurate.

COLORAMICS, LLC does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.

For more information in AUSTRALIA see web site [www.nohsc.gov.au](http://www.nohsc.gov.au)