

MATERIAL SAFETY DATA SHEET

SECTION 1: MATERIAL INFORMATION AND USE

Material Name: **ProFaux Crackle Additive**
WHMIS Classification: Not WHMIS CONTROLLED
Material Use: Decorative Finishes
Manufacturer: TEXTURLINE 170 Wikinson rd Brampton Ontario L6T 4Z5 Email textur@attcanada.com

SECTION 2: COMPONENT INFORMATION

Ingredients:	CAS, NA or UN number
Acrylic copolymer emulsions	Unknown
Surfactant	Unknown
Water	7732 - 18 - 5
Coalescing agents	57 - 55 - 6

SECTION 3: PHYSICAL DATA FOR MATERIAL

PHYSICAL STATE Liquid	ODOUR THRESHOLD N/D	VAPOUR PRESSURE N/D
VAPOUR DENSITY (Air = 1) < 1 Water	EVAPORATION RATE (N-Butylacetate = 1) < 1 Water	SPECIFIC GRAVITY 1.0 @ 23oC
BOILING POINT 100 Celsius Degrees Water	MELTING POINT 0 Celsius Degree Water	DENSITY (g/ml) 1.0 @ 23 oC
SOLUBILITY IN WATER (g/ml @ 20c) Miscible	% SOLIDS 25 +- 5	pH 7.5

SECTION 4: FIRE AND EXPLOSION HAZARDS

FLAMMABILITY: YES: _____ NO: x

SECTION 5: TOXICOLOGICAL PROPERTIES OF MATERIAL

SKIN ABSORPTION: No evidence of harmful effects from available information
EYE CONTACT: May cause irritation
INGESTION: May cause irritation of stomach with abdominal discomfort

SECTION 6: FIRST AID MEASURES

SKIN: Flush with running water.
EYE: Flush eyes with water. Contact physician if discomfort persists.
INHALATION: Move victim to fresh air. Contact physician if symptoms persist.
INGESTION: If victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomits, rinse mouth and administer more water. Obtain medical attention.

MAY 2002