



<b>Quick Identifier:</b> Common Name (used on label and list)	Product Code:	Packaging:	<b>Quick Identifier:</b> Common Name (used on label and list)	Product Code:	Packaging:
Vella Wax - Clear	30001	6 lb pail	Vella Wax - Clear	30008	22 oz. pail
Vella Wax – Walnut	30005	6 lb pail	Vella Wax - Clear	30009	22 oz. pail
Vella Wax – Mahogany	30007	6 lb pail	Vella Wax - Clear	30010	22 oz. pail

<b>Section 1 – Product Name &amp; Synonyms:</b>		Vella Wax	
<b>Manufacturer’s Name</b>	Specialized Building Products, LLC	<b>Emergency Telephone: (24 hour service)</b>	Chemtrec @ 800-422-9300
<b>Street</b>	145 W. Meats Ave.	<b>Other Information:</b>	714-279-1042
<b>City, State, and ZIP</b>	Orange, CA 92865	<b>FAX:</b>	714-279-1043
<b>Date Prepared:</b>	March 29, 2006	<b>Web-Site</b>	Specializedbuildingproducts.com

<b>Section 2 – Hazardous Ingredients / Identity</b>				
<i>THE ABOVE PRODUCTS MAY CONTAIN THE FOLLOWING COMPONENTS</i>				
Hazardous Component(s) Chemical & Common name:	OSHA PEL	ACGIH TLV	% - Optional	CAS Number
D-Limonene – Orange Terpenes	N/A	N/A		5989-27-5
Stoddard Solvent	N/A	100 ppm		8052-41-3
<p>* Respirable fraction (PEL)  ** Total dust (PEL) or Inhalable Particulate (TLV)  *** STEL/CEIL – STEL stands for Short-Term Exposure Limit. Usually a 15 – minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hour TWA has not been exceeded. CEIL stands for Ceiling (C) - the concentration that shall not be exceeded during any part of the working exposure.  SEN – TLV-Confirmed potential for worker sensitization as a result of dermal contact and/or inhalation exposure, based on the weight of scientific evidence  NIC – TLV Notice of Intended Changes</p> <p><sub>1</sub> - Present as a natural occurring contaminant, ACGIH Threshold limit values lists Silica-Crystalline Quartz as “A2- Suspected Human Carcinogen”  <sub>2</sub> - &lt;1% crystalline silica.  (e) - The value is for particulate matter containing no asbestos and &lt;1% crystalline silica.  <sub>R</sub> - Respirable fraction, fraction passing a size selector with the characteristics defined in the “C” Paragraph of Appendix D in the current TLV booklet.</p>				

<b>OTHER INGREDIENTS / IDENTITY</b>			
Hazardous Component(s) Chemical & Common name:	OSHA PEL	% - Optional	CAS Number
Combustible; Otherwise Non-Hazardous Ingredients – Proprietary Blend of Waxes	N/A	N/A	N/A

<b>SECTION 3 – PHYSICAL &amp; CHEMICAL CHARACTERISTICS</b>			
Boiling Point	350° F	Solubility in Water	Less than 3%
Specific Gravity (H <sub>2</sub> O = 1)	0.886	Reactivity in Water	N/A
Vapor Pressure (mm Hg)	N/A	Melting Point	180° F
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Insoluble	Water Reactive	No
Appearance and Odor	Orange waxy solid – citrus odor		

<b>SECTION 4 – FIRE &amp; EXPLOSION DATA</b>			
Flash Point	109° F TCT	Non-Combustible (?)	No
Auto-Ignition Temperature	N/A	Flammability Limits in Air (% volume)	N/A
Special Fire Fighting Procedures	None	LEL Lower	N/A
Unusual Fire and Explosion Hazards	None	UEL Upper	N/A
Extinguishing Media	Dry Chemical		

<b>SECTION 5 – PHYSICAL HAZARDS (REACTIVITY DATA)</b>			
Stability	Unstable [ ]		Stable [ X ]
Conditions to Avoid	<ul style="list-style-type: none"> <li>Excessive Heat</li> <li>Polymerization catalysts such as Aluminum Chloride</li> </ul>		
Incompatibility (Materials to Avoid)	Strong oxidizing agents – Peroxides, Halogens, Vinyl Chloride		
Hazardous Decomposition Products	Releases CO <sub>x</sub> when heated to decomposition		
Hazardous Polymerization	Will Not Occur [ X ]		May Occur [ ]

<b>SECTION 6 – HEALTH HAZARDS</b>						
Acute	May irritate digestive tract if ingested.			Chronic	N/A	
Signs and symptoms of Exposure				Possible Nausea		
Medical Condition Generally Aggravated by Exposure				None Known		
Chemical Listed as Carcinogen or Potential Carcinogen		ACGIH TLV [N]	NIOSH Yes [N]	NTP Yes [N]	IRAC Monograph [N]	OSHA Yes [N]
Y – Yes N – No or Not established P-Potential						
Emergency and First Aid Procedures	Persons exposed to large amounts of airborne dust should leave the area to avoid the nuisance particulate material					
Routes of Entry	Inhalation	N/A				
	Eyes	Flush eyes with clean water for 15 minutes				
	Skin	Wash affected area with soap and water				
	Ingestion	DO NOT INDUCE VOMITING. Drink one glass of water & call physician				

<b>SECTION 7 – SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES</b>				
Precautions to be taken in Handling and Storage		Keep away from heat or flame; Properly dispose of used cloths.		
Other Precautions		Use precaution for combustible materials.		
Steps to be Taken in Case Material is Released or Spilled		If the material is in a molten state, allow it to solidify.		
Waste Disposal Methods		Dispose of in accordance with all federal, state, and local regulations		
HMIS Rating	Health = 0	Flammability = 2	Reactivity = 0	Personal Protection = G

<b>SECTION 8- SPECIAL PROTECTION INFORMATION/CONTROL MEASURES</b>			
Respiratory Protection (specify type)	Not normally required.		
Ventilation	Local exhaust preferred; Mechanical Exhaust satisfactory	Special N/A	Other N/A
Protective Gloves	Yes		
Eye Protection	Safety glasses or goggles		
Other Protective Clothing or Equipment	None		
Work / Hygienic Practices	Wash hands with soap and water after handling.		

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. Specialized Building Products, LLC., MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HERIN. Specialized Building Products, LLC., will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.