

Section 1 – General Information

Manufacturer: <u>HMIS Rating</u>

Modern Masters, Inc.

13201 Saticoy Street,

North Hollywood, California 91605

REACTIVITY

0

818-765-2915

Emergency Telephone: 800-942-3166 Preparation Date: April 4, 2003

Product Name: Decorative Painter's "Satin Varnish" Water-based Varnish

Product Code: DP-610

Section 2 – Hazardous Ingredients

Hazardous Component	CAS #	OSHA PEL	ACGIH TLV
Amorphous Fumed Silica	112945-52-5	20 ppm	10 ppm
Propanol, (2-Methoxymethylethoxy)-	34590-94-8	150 ppm	100 ppm

Section 3 - Hazard Identification

Emergency Overview: This material is a clear varnish. It is a stable, non-flammable, translucent flowable liquid with a flash point above 200°F.

Primary Routes of Exposure:

Inhalation Skin contact Eye contact

Potential Acute Health Effects:

Inhalation: May cause respiratory tract irritation **Eye**: May cause eye irritation

Est.: Estimated 818-765-2915

Page 1 of 7 pages

Skin: Prolonged or repeated skin contact may cause irritation

Ingestion: Not hazardous under intended use conditions

Potential Chronic Health Effects: None known



SECTION 4 – FIRST AID MEASURES

Eye contact: Flush eyes with clean water for at least 15 minutes. Seek medical attention.

Skin contact: Thoroughly wash with soap and warm water immediately. Thoroughly wash all contaminated clothing. Seek medical attention if irritation persists.

Inhalation: If irritation occurs, remove to fresh air and seek medical attention if cough or other symptoms develop.

Ingestion: Do not induce vomiting. Seek medical attention.

Note to Physician: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point (method): N/D (est. >200°F)

Extinguishing Media:Use water spray, foam, or carbon dioxide when fighting fires involving this material.

Protection of Firefighters: As in any fire, wear NIOSH approved self-contained breathing apparatus pressure-demand and full protective gear.

Fire and Explosion Hazards: Material will not burn.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Slippery: can cause slips and falls if walked on.

Clean Up Methods: Contain spill with sand or other diking material. Soak up small spills with absorbent material. Dispose of in accordance with federal, state, and local regulations.

Est.: Estimated

Page 2 of 7 pages

818-765-2915

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment.)



SECTION 7 - HANDLING AND STORAGE

Handling: Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash hands with soap and warm water after use.

Storage: KEEP PRODUCT FROM FREEZING. Keep container tightly closed when not in use. Do not reuse container and properly dispose of after use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: If necessary, use general room dilution ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Eye contact should be avoided. Where eye contact is likely, wear chemical splash goggles and/or full-face shield.

Skin Protection: Wear impervious gloves to prevent prolonged skin contact. Wear proper protective clothing to prevent skin contact.

Respiratory Protection: None needed under normally anticipated use conditions. If vapor levels exceed allowable limits, wear a NIOSH approved air-purifying respirator with an organic vapor cartridge.

General Hygiene Practices: Avoid eye and skin contact. Avoid breathing vapors. Wash hands with soap and warm water before eating, drinking, or using the toilet.

Est.: Estimated

Page 3 of 7 pages

818-765-2915



SECTION 9 - PHYSICAL DATA

Appearance: Translucent flowable liquid Odor: Mild odor

Physical State: Liquid pH: 4 to 10

Boiling Point: Above 200°F **Melting Point**: <32°F

Vapor Pressure: N/D **Vapor Density**: N/D

Odor Threshold: N/D Viscosity: 1000 to 10,000 cps

Solubility in Water: Dilutable in water **Specific Gravity** (water = 1): 1.02 to 1.2

Material VOC: Material, less water, contains less than 450 grams per liter Volatile Organic

Compounds.

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable, non-reactive Incompatibility: Strong acids and strong bases

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: None known

SECTION 11 – TOXICOLOGICAL INFORMATION

Carcinocenicity: This material is not considered a carcinogen by IARC or NTP and is not regulated as a carcinogen by OSHA.

Est.: Estimated

Page 4 of 7 pages

818-765-2915

(See also Section 15 for related information.)



SECTION 12 - ECOLOGICAL INFORMATION

Chemical Fate and Effects: No data available.

Section 13 – Disposal Considerations

Recommended Waste Disposal Method: This material is not considered hazardous waste under Federal Hazardous Waste Regulations (40CFR 261). However, state and local requirements for waste disposal may be more restrictive or otherwise differ from federal regulations. Chemical additions, processing, or otherwise altering this material may render the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate. Consult all applicable federal, state, and local regulations regarding the proper disposal of this material.

Section 14 - Transportation Information

Regulated by the DOT: Not regulated

DOT Proper Shipping Name: Paint

<u>Section 15 – Regulatory Information</u>

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

Est.: Estimated

Page 5 of 7 pages

818-765-2915

<u>Chemical Name</u> <u>CAS #</u> <u>Maximum Concentration (Wt. %)</u>

none N/A N/A



SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311, and 312).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u> <u>CAS #</u> <u>Maximum Concentration (Wt. %)</u>

none N/A N/A

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u> <u>CAS # Maximum Concentration (Wt. %)</u>

Amorphous Fumed Silica 112945-52-5 0.2%

Propanol, (2-Methoxymethylethoxy)- 34590-94-8 2.0%

TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation.

Est.: Estimated

Page 6 of 7 pages

818-765-2915



<u>Section 16 – Other Information</u>

Legend: N/A: Not Applicable N/D: Not Determined

N/E: Not Established
STEL: Short Term Exposure Limit

N/R: Not Required
C: Ceiling Value

cps: Centipoise mg/m³: milligrams per cubic centimeter

PPM: Parts Per Million **PPB**: Parts Per Billion

PEL: Permissible Exposure Limit **TLV**: Time Weighted Average

mppcf: million particles per cubic foot of air

ACGIH: American Conference of Governmental Industrial Hygienists

CPSC: Consumer Product Safety Commission **DOT:** US Department of Transportation **FHSA:** Federal Hazardous Substance Act

OSHA: Occupational Safety and Health Administration (US Dept. of Labor)

RCRA: Resource Conservation and Recovery Act

SARA: Superfund Amendment and Reauthorization Act

TSCA: Toxic Substance Control Act

HMIS Key

4 = Severe Hazard

3 = Serious Hazard

2 = Moderate Hazard

1 = Slight Hazard

0 = Minimal Hazard

Prepared by: Modern Masters Regulatory Compliance Manager,

Technical Management Department

7340 Greenbush Avenue, North Hollywood, California 91605 (818) 765-2915

Est.: Estimated

818-765-2915

Page 7 of 7 pages

Disclaimer: Modern Masters, Inc. believes, to the best of its knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data to comply with all applicable international, federal, state, and local laws and regulations.