



# MATERIAL SAFETY DATA SHEET

## SECTION 1 – GENERAL INFORMATION

**Manufacturer:**

Modern Masters®, Inc.  
9380 San Fernando Road,  
Sun Valley, California 91352  
818-683-0201

**HMIS Rating**

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0

**Emergency Telephone:** 800-942-3166

**Preparation Date:** September 7, 2006

**Revision Date:** December 4, 2006

**Product Name:** “Texture Effects” Water-based 100% Acrylic Texturing Medium

**Product Code:** TEX100

## SECTION 2 – HAZARDOUS INGREDIENTS

<u>Hazardous Component</u>	<u>CAS #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
----------------------------	--------------	-----------------	------------------

none

## SECTION 3 – HAZARD IDENTIFICATION

**Emergency Overview:** This material is a 100% acrylic texturing medium. It is a stable, non-flammable, opaque, viscous liquid with a flash point above 200°F.

**Primary Routes of Exposure:**

Inhalation	Skin contact	Eye contact
------------	--------------	-------------

**Potential Acute Health Effects:**

**Inhalation:** May cause respiratory tract irritation      **Eye:** May cause eye irritation

**Skin:** Prolonged or repeated skin contact may cause irritation

**Ingestion:** Not hazardous under intended use conditions

**Potential Chronic Health Effects:** None.



# MATERIAL SAFETY DATA SHEET

---

## SECTION 4 – FIRST AID MEASURES

- Eye contact:** Flush eyes with clean water for 15 minutes. Seek medical attention, especially if irritation persists.
- Skin contact:** Thoroughly wash with soap and water before the binder dries.
- Inhalation:** If irritation occurs, remove to fresh air and seek medical attention if cough or other symptoms develop.
- Ingestion:** Do not induce vomiting. Seek medical attention.
- Note to Physician:** Treat symptomatically. This material is basically non-toxic. A small quantity (approximately one tablespoon) is unlikely to cause harm.

## SECTION 5 – FIRE FIGHTING MEASURES

- Flash Point (method):** N/D (est. >200°F)
- Extinguishing Media:** Use water spray, foam, or carbon dioxide when fighting fires involving this material.
- Protection of Firefighters:** As in any fire, wear NIOSH approved self-contained breathing apparatus pressure-demand and full protective gear.
- Fire and Explosion Hazards:** Material will not burn.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Slippery: can cause slips and falls if walked on.
- Clean Up Methods:** Contain spill with sand or other diking material. Soak up small spills with absorbent material. Dispose of in accordance with federal, state, and local regulations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment.)



# MATERIAL SAFETY DATA SHEET

---

## SECTION 7 – HANDLING AND STORAGE

**Handling:** Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash hands with soap and warm water after use.

**Storage:** Keep from freezing. Keep container tightly closed when not in use. Do not reuse container and properly dispose of container when empty.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** If necessary, use general room dilution ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

### Personal Protective Equipment (PPE):

**Eye Protection:** Eye contact should be avoided. Where eye contact is likely, wear chemical splash goggles and/or full-face shield.

**Skin Protection:** Wear gloves to prevent prolonged skin contact.

**Respiratory Protection:** None needed under normally anticipated use conditions. If vapor levels exceed allowable limits, wear a NIOSH approved air-purifying respirator with an organic vapor cartridge.

**General Hygiene Practices:** Avoid eye and skin contact. Avoid breathing vapors. Wash hands with soap and warm water before eating, drinking, or using the toilet.



# MATERIAL SAFETY DATA SHEET

---

## SECTION 9 – PHYSICAL DATA

**Appearance:** Opaque, off-white, viscous liquid    **Odor:** Mild odor  
**Physical State:** Viscous liquid    **pH:** 7 to 10  
**Boiling Point:** Above 200°F    **Melting Point:** <32°F  
**Vapor Pressure:** N/D    **Vapor Density:** N/D  
**Odor Threshold:** N/D    **Viscosity:** 300,000-3,000,000 cps  
**Solubility in Water:** Dilutable in water    **Specific Gravity (water = 1):** 1.1 to 1.4  
**Material VOC:** Material, less water, contains less than 50 grams per liter Volatile Organic Compounds.

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:** Stable, non-reactive    **Incompatibility:** Strong acids and strong bases  
**Hazardous Polymerization:** Will not occur  
**Hazardous Decomposition Products:** None known

## SECTION 11 – TOXICOLOGICAL INFORMATION

**Carcinogenicity:** This material is not considered a carcinogen by IARC or NTP and is not regulated as a carcinogen by OSHA.

(See also Section 15 for related information.)

## SECTION 12 – ECOLOGICAL INFORMATION

**Chemical Fate and Effects:** No data available.



# MATERIAL SAFETY DATA SHEET

---

## SECTION 13 – DISPOSAL CONSIDERATIONS

**Recommended Waste Disposal Method:** This material is not considered hazardous waste under Federal Hazardous Waste Regulations (40CFR 261). However, state and local requirements for waste disposal may be more restrictive or otherwise differ from federal regulations. Chemical additions, processing, or otherwise altering this material may render the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate. Consult all applicable federal, state, and local regulations regarding the proper disposal of this material.

## SECTION 14 – TRANSPORTATION INFORMATION

**Regulated by the DOT:** Not regulated

**DOT Proper Shipping Name:** Paint

## SECTION 15 – REGULATORY INFORMATION

### CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Maximum Concentration (Wt. %)</u>
none	N/A	N/A



# MATERIAL SAFETY DATA SHEET

---

## **SARA Title III, section 311/312:**

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311, and 312).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Maximum Concentration (Wt. %)</u>
none	N/A	N/A

## **SARA Title III, section 313:**

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Maximum Concentration (Wt. %)</u>
Crystalline Silica	14808-60-7	<0.01%
Acrylamide	79-01-6	<0.001%

## **TSCA:**

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation.

