

Cassiopeia

Glass Flakes on a Flexible Base

Product Description

A set comprising Cassiopeia base acrylic paint, which serves as an infrastructure for glitter and glass balls of various sizes applied to it by spraying. An innovative effect that creates the feeling of an unfinished wall with illusions of light and color. A finish with glass flakes only is available, as well as with the addition of crystal sparkles.

Typical Uses

On any existing infrastructure for exterior and interior walls, wood, plaster, gypsum and more.

Surface

Apply PVA primer.

Application

1. Apply one coat of Cassiopeia Base with a delicate roller and wait until fully cured.
2. Apply a second coat of Cassiopeia Base with a thicker roller. The thickness of that should be 1 kg/m². When the substance is still wet, spray the glitter and glass flakes on the wall until a complete and uniform appearance is obtained (300-400 gr. of flakes / m²).
3. After the wall is dry, go over it with a brush and remove any protruding flakes (to prevent injury).
4. PLC Lacquer can be applied to the entire surface.

Application

Cassiopeia Base colored is shaded in accordance with any color fan, with roller or compressor spraying. The glitter and glass flakes are to be applied with spray gun with an aperture (nozzle) at least 4mm wide (in order to enable the glass flakes to exit). The most attractive appearance is obtained when background is dark and the glass flakes sparkle on it in a wide range of colors.

Our expert's recommendation

Practice the spraying technique on a small area before starting the project. Cover the floor with clean polyethylene sheeting and collect the glitter and glass flakes that drop, for reuse.

Lighting: Lighting plays a decisive role in the final appearance. We recommend spotlights illumination at a distance of three meters, in order to obtain a splendid look.

Shades

Can be shaded using any color fan.

Shelf-life & Packaging

Super Flexible 1 kg and 5kg

Glass flakes

Health and safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Meoded Paint's & Decoration. General Notes: The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.